

SPECIFIC TECHNICAL CRITERIA

UL 60950-1, First Edition Information technology equipment - Safety- Part 1: General Requirements	
Report Reference No	E193009-A10-UL-1
Compiled by	Rudy Manzano
Reviewed by	Bob Hilbrecht
Date of issue	2006-04-17
Standards	UL 60950-1:2003, First Edition CSA C22.2 No. 60950-1-03 1st Ed. April 1, 2003
Test procedure	Component Recognition
Non-standard test method	N/A
Test item description	DC-DC Converter
Trademark	None
Model and/or type reference	DOWx-yTz1z1z1z1z1z1, where w can be "S" or "H"; x can be 06, 10, or 16; y can be 05 or 12; z1 can be "-", "/", any alphanumeric character, or blank.
Rating(s)	See Enclosure Miscellaneous "Electrical Rating"

GENERAL PRODUCT INFORMATION:	
CF1.0	Engineering Conditions of Acceptability
CF1.1	For use only in or with complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc. When installed in an end-product, consideration must be given to the following:
CF1.5	The following secondary output circuits are SELV: Output(s) for all models.
CF1.11	The power supply terminals and/or connectors are: Suitable for factory wiring only
CF1.12	The maximum investigated branch circuit rating is: Tests conducted with external very fast-acting type fuse, rated 20A, 125Vdc. ,
CF1.13	The investigated Pollution Degree is: 2
CF1.15	Proper bonding to the end-product main protective earthing termination is: Not required
CF1.16	An investigation of the protective bonding terminals has: Not been conducted
CF1.19	The following end-product enclosures are required: Mechanical, Fire, Electrical
CF1.21	The maximum continuous power supply output (Watts) relied on forced air cooling from: See Miscellaneous, "Fan Location", for detail. Air-flow is at 500 L.F.M.