

## ELECTRICAL RATING (CONTINUED):

Model	Input (dc)		Output (dc)	
	V	mA	V	mA
PFKC05-12S33Z-Z1Z1Z1	9-18 or 12	540	3.3	1000
PFKC05-12S05Z-Z1Z1Z1	9-18 or 12	772	5	1000
PFKC05-12S12Z-Z1Z1Z1	9-18 or 12	825	12	470
PFKC05-12S15Z-Z1Z1Z1	9-18 or 12	878	15	400
PFKC05-12D05Z-Z1Z1Z1	9-18 or 12	761	±5	±500
PFKC05-12D12Z-Z1Z1Z1	9-18 or 12	807	±12	±230
PFKC05-12D15Z-Z1Z1Z1	9-18 or 12	834	±15	±190
PFKC05-24S33Z-Z1Z1Z1	18-36 or 24	270	3.3	1000
PFKC05-24S05Z-Z1Z1Z1	18-36 or 24	370	5	1000
PFKC05-24S12Z-Z1Z1Z1	18-36 or 24	407	12	470
PFKC05-24S15Z-Z1Z1Z1	18-36 or 24	433	15	400
PFKC05-24D05Z-Z1Z1Z1	18-36 or 24	376	±5	±500
PFKC05-24D12Z-Z1Z1Z1	18-36 or 24	399	±12	±230
PFKC05-24D15Z-Z1Z1Z1	18-36 or 24	390	±15	±190
PFKC05-48S33Z-Z1Z1Z1	36-75 or 48	133	3.3	1000
PFKC05-48S05Z-Z1Z1Z1	36-75 or 48	188	5	1000
PFKC05-48S12Z-Z1Z1Z1	36-75 or 48	204	12	470
PFKC05-48S15Z-Z1Z1Z1	36-75 or 48	217	15	400

## ELECTRICAL RATING (CONTINUED):

Model	Input (dc)		Output (dc)	
	V	mA	V	mA
PFKC05-48D05Z-Z1Z1Z1	36-75 or 48	190	±5	±500
PFKC05-48D12Z-Z1Z1Z1	36-75 or 48	200	±12	±230
PFKC05-48D15Z-Z1Z1Z1	36-75 or 48	206	±15	±190

\*  
\*  
\*  
\*  
\*  
\*  
\*  
\*  
\*  
\*  
\*  
\*  
\*

Conditions of Acceptability - When installed in the end-product, consideration shall be given to the following:

1. **This component has been judged on the basis of required spacing in the Standard for Safety of Information Technology Equipment, CAN/CSA C22.2 No. 60950-1 and UL 60950-1 First Edition, dated April 1, 2003, Sub-clause 2.10, which would cover the component itself if submitted for Listing.**
2. The products were tested on a 5 A time delay fuse protection circuit. If used on a protection circuit greater than this, additional testing may be necessary.
3. All secondary output circuits are SELV and are not hazardous energy levels.
4. The terminals and connectors are suitable for factory wiring only.
5. The equipment has been evaluated for use in a Pollution Degree 2 environment.
6. A suitable Electrical and Fire enclosure shall be provided.
7. The component is intended to be connected to isolated secondary circuit which is separated from primary circuit by Reinforced or Double insulation.
8. **All models withstood 3200 V dc Electric Strength Test.**